

# DH-IPC-HDBW4631R-AS

6MP WDR IR Dome Network Camera



## OVERVIEW

- . 1/2.9" 6Megapixel progressive scan CMOS,Max20fps@6M(3072×2048)
- . H.265&H.264 dual codec
- . WDR(120dB),Day/Night(ICR),3DNR,AWB,AGC,BLC
- . Smart Detection,mobile APP
- . Multiple network monitoring:Web viewer,CMS(DSS/PSS)&DMSS
- . Max. IR LEDs Length 30m
- . Micro SD memory 128G maximum,IP67,IK10,PoE



## System Overview

The IR Megapixel Vari-focal camera delivers 6MP resolution with a 2.7mm ~13.5mm varifocal lens. The camera's elegant blend of aesthetics combined with a range of easy mounting solutions provides an excellent choice for a variety of small to mid-size applications at an affordable price.

## Functions

### Smart Codec (H.265 & H.264)

Smart Codec is the optimized implementation of standard video compression (H.265 & H.264) that uses a scene-adaptive encoding strategy, dynamic GOP, dynamic ROI, flexible multi-frame reference structure and intelligent noise reduction to deliver high-quality video without straining the network. Smart Codec technology reduces bit rate and storage requirements by up to 70% when compared to the standard video compression.

### Intelligent Video analysis (IVS)

Dahua camera is equipped with a built-in intelligent analytic algorithm based on video, which can realize intelligent functions like Tripwire and Intrusion, to quickly and accurately respond to monitoring events in specific area. It can enhance monitoring efficiency. In addition, the camera supports intelligent tamper detection, which is to generate warning message via detecting dramatic scene change and to guarantee effective video surveillance.

### Wide Dynamic Range (WDR)

The camera achieves vivid images, even in the most intense contrast lighting conditions, using industry-leading wide dynamic range (WDR) technology. For applications with both bright and low lighting conditions that change quickly, true WDR (120 dB) optimizes both the bright and dark areas of a scene at the same time to provide usable video.

### Smart IR Technology

With IR illumination, detailed images can be captured in low light or total darkness. The camera's Smart IR technology adjusts the intensity of camera's infrared LEDs to compensate the distance of an object. Smart IR technology prevents IR LEDs from whitening out images as they come closer to the camera. The camera's integrated infrared illumination provides high performance in extreme low-light environments up to 30m (98ft).

### Protection (IP67, IK10, wide voltage)

The camera allows for  $\pm 25\%$  input voltage tolerance, suitable for the most unstable conditions for outdoor applications. Its 2KV lightning rating provides effective protection for both the camera and its structure against lightning. Subjected and certified to rigorous dust and immersion tests (IP67) and impact tests (IK10), The camera complies with an IK10 impact rating making it capable of withstanding the equivalent of 5 kg (11.02 lbs) of force dropped from a height of 40 cm (15.75 in.)

### Environmental

Dahua cameras operate in extreme temperature environments, rated for use in temperatures from -30° C to +60° C (-22° F to +140° F) with 95% humidity.

### Image flip

Capturing unnecessary data such as surrounding hallway walls can increase storage requirements without any added value. The image flip feature allows the camera's image to be rotated in 90° increments for better video optimization.

### Interoperability

The camera conforms to the ONVIF (Open Network Video Interface Forum) specifications, ensuring interoperability between network video products regardless of manufacturer.

Technical Specification					
Camera					
Image Sensor		1/2.9"6Megapixel progressive scan CMOS			
Effective Pixels		6MP (3072×2048)			
RAM/ROM		512MB/32MB			
Scanning System		Progressive			
Electronic Shutter Speed		Auto/Manual, 1/3~1/100000s			
Minimum Illumination		0.03Lux/F1.4( Color,1/3s,30IRE) 0.3Lux/F1.4( Color,1/30s,30IRE) 0Lux/F1.4(IR on)			
S/N Ratio		More than 56dB			
IR Distance		Distance up to 30M			
IR On/Off Control		Auto/ Manual			
IR LEDs		1			
Lens					
Lens Type		Fixed			
Mount Type		M12			
Focal Length		2.8mm (3.6mm, 6mm optional)			
Max. Aperture		F2.5 (F2.2, F2.0)			
Angle of View		H:99° (70°, 47.34°), V:69.4° (48°, 33.75°)			
Focus Control		Fixed			
Close Focus Distance		2.8mm: 0.8m/3.6mm:1.2m/6mm:3.9m			
DORI Distance	Lens	Detect	Observe	Recognize	Identify
	W	64m(210ft)	26m(85ft)	13m(43ft)	6m(20ft)
	T	222m(728ft)	89m(292ft)	44m(144ft)	22m(72ft)
PTZ					
Pan/Tilt Range		N/A			
Intelligence					
Event Trigger		Motion detection, Video tampering,Scene changing,Network disconnection,IP address conflict,Illegal access,Storage anomaly			
IVS		Tripwire, Intrusion			
Video					
Compression		H.265/H.264/MJPEG			
Smart Codec		Support H.265+/h.265+			
Streaming Capability		3 Streams			
Resolution		(2688x1520)/(2560x1440)/ (2304x1296)/1080P(1920x1080)/ SXGA(1280x1024)/1.3M(1280× 960)/720P(1280×720)/ D1(704×576/704×480)/VGA(640×480) CIF(352×288/352×240)			
Frame Rate		Main Stream: 4M (1 ~ 20fps)/3M(1 ~ 25/30fps)			
		Sub Stream: D1(1 ~ 20/25fps)			
Bit Rate Control		CBR/VBR			
Bit Rate		H.265: 12K ~ 8448Kbps H.264: 32K ~ 10240Kbps			

Day/Night	Auto(ICR) / Color / B/W
BLC Mode	BLC / HLC / WDR(120dB)
White Balance	Auto/Natural/Street Lamp/Outdoor/Manual
Gain Control	Auto/Manual
Noise Reduction	3D DNR
Motion Detection	Off / On (4 Zone, Rectangle)
Region of Interest	Off / On (4 Zone)
Electronic Image Stabilization(EIS)	N/A
Smart IR	Support
Digital Zoom	16x
Flip	0°/90°/180°/270°
Mirror	Off / On
Privacy Masking	Off / On (4 Area, Rectangle)

Audio	
Compression	G.711a/ G.711Mu/ AAC/ G.726

Network	
Ethernet	RJ-45 (10/100Base-T)
Protocol	HTTP; TCP; ARP; RTSP; RTP; UDP; SMTP; FTP; DHCP; DNS; DDNS; PPPOE; IPv4/v6; QoS; UPnP;NTP;IGMP; SNMP
Interoperability	ONVIF Profile S&G,API
Streaming Method	Unicast / Multicast
Max. User Access	10 Users
Edge Storage	NAS Local PC for instant recording Micro SD Card 128GB
Web Viewer	IE, Chrome, Firefox, Safari
Management Software	Smart PSS, GDMSS,IDMSS, Easy4ip
Smart Phone	IOS, Android

Certifications	
Certifications	CE (EN 60950:2000) UL:UL60950-1 FCC: FCC Part 15 Subpart B

Interface	
Video Interface	N/A
Audio Interface	1 RCA LINE IN , 1 RCA LINE OUT
RS485	N/A
Alarm	2 line in, 2 line out

Electrical	
Power Supply	DC12V, PoE (802.3af)(Class 0)
Power Consumption	<7.2W


Environmental

Operating Conditions	-30° C ~ +60° C (-22° F ~ +140° F) / Less than 95% RH
Storage Conditions	-30° C ~ +60° C (-22° F ~ +140° F) / Less than 95% RH
Ingress Protection	IP67
Vandal Resistance	IK10

Construction

Casing	Metal
Dimensions	φ122mm×88.9mm(4.80"x3.50")
Net Weight	0.4Kg (0.88lb)
Gross Weight	0.54Kg(1.19lb)

Dimensions (mm/inch)



Accessories

Optional:



Junction Mount	Inceiling Mount
PFA137	PFB200C
Wall Mount	Pole Mount
PFB203W	PFB203W + PFA152-E
Wall Mount with Rain Shade	Pole Mount with Rain Shade
PFA137+PFA200W	PFA137+PFA152-E+PFA200W