

## DH-IPC-HFW8281E-Z

---

### 2MP Starlight WDR Ultra-Smart Network Camera



### Features

- 1/1.9" 2 Megapixel progressive scan CMOS
- Support H.264,MJPEG dual codec
- Smart triple streams supported
- Max 50/60fps@1080P
- Starlight: 0.005Lux/F1.65 (Color)
- Ultra WDR (Wide Dynamic Range) up to 120dB
- Ultra 3D DNR
- Ultra Defog, ROI, EIS
- Smart detection
- Intelligent Function
- 4~8mm varifocal motorized lens

## DH-IPC-HFW8281E-Z

- Technical Specifications**


Model	DH-IPC-HFW8281EP-Z	DH-IPC-HFW8281EN-Z
<b>Camera</b>		
Image Sensor	1/1.9" 2Megapixel CMOS	
Effective Pixels	1920(H)x1080(V)	
Scanning System	Progressive	
Electronic Shutter Speed	Auto/Manual, 1/3~1/10000s	Auto/Manual, 1/4~1/10000s
Min. Illumination	0.005Lux/F1.65 (Color),0Lux/F1.65(IR on)	
S/N Ratio	More than 50dB	
Video Output	1 port	
<b>Camera Features</b>		
Max. IR LEDs Length	50m	
Day/Night	Auto(ICR)/Color/B/W	
Backlight Compensation	BLC / HLC / WDR(120 dB)	
White Balance	Auto/Manual	
Gain Control	Auto/Manual	
Noise Reduction	3D	
Privacy Masking	Up to 4 areas	
EIS	Support	
Ultra Defog	Support	
<b>Lens</b>		
Focal Length	4~8mm motorized	
Max Aperture	F1.65	
Focus Control	Auto	
Angle of View	H:90°(Wide)~58°(Tele)	
Lens Type	Motorized /Auto Iris(DC)	
Mount Type	Board-in type	
<b>Video</b>		
Compression	H.264/H.264B/H.264H/MJPEG	
Resolution	1080P(1920×1080)/720P(1280×720)/D1(704×576)/CIF(352×288)	1080P(1920×1080)/720P(1280×720)/D1(704×480)/CIF(352×240)
Frame Rate	Main Stream	1080P/720P(1 ~ 50/60fps)
	Sub Stream	D1/CIF(1 ~ 25/30fps)
	Third Stream	1080P/720P/D1(1 ~ 25/30fps)
Bit Rate	H.264: 32K ~ 8192Kbps	
ROI	Up to 4 areas	
<b>Audio</b>		
Compression	G.711a/G.711u	
Interface	1/1 channel In/Out	
<b>Smart Function</b>		
	Tripwire	

## DH-IPC-HFW8281E-Z

Smart detection	Intrusion
	Scene change
	Missing/Abandoned
	Audio detect
	Defocus detect
	Face detect
Intelligent function	People counting
	Heat map
<b>Network</b>	
Ethernet	RJ-45 (10/100Base-T)
Wi-Fi	N/A
Protocol	IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS, Bonjour
Compatibility	ONVIF, PSIA, CGI
Max. User Access	20 users
Smart Phone	iPhone, iPad, Android, Windows Phone
<b>Auxiliary Interface</b>	
Memory Slot	Micro SD, Max 128GB
Alarm	2/1 channel In/Out
<b>General</b>	
Power Supply	DC12V(AC24V optional), PoE (802.3af)
Power Consumption	<12.5W
Working Environment	-30°C~+60°C, Less than 95% RH
Ingress Protection	IP66
Dimensions	273.30mm × 94.8mm× 94.8mm
Weight	1.25kg

# DH-IPC-HFW8281E-Z

## Dimensions (mm)



## Accessory (optional)

