

Off-Grid Solar Inverter

Single Phase - IP20 - High Frequency

Model: MR-SPF4000 / 6000 TWIN (Version 4)

FEATURES

- Dual output for smart load management
- Maximum PV input current 27A
- Customizable status LED ring with RGB lights
- Touchable button with large 4.3" colored LCD
- Built-in Wifi for mobile monitoring (Android/iOS App available)
- Supports USB On-the-Go function
- Data log event stored in the inverter
- Reserved communication port (RS485, CAN-BUS or RS232) for BMS
- Battery independent design
- Battery equalization extends lifecycle
- Enhanced charging power
- Built-in anti-dust kit



SPECIFICATIONS

MODEL	MR-SPF4000 TWIN (Version 4)	MR-SPF6000 TWIN (Version 4)
RATED POWER	4000VA / 4000W	6000VA / 6000W
INPUT		
Nominal Input Voltage	230VAC	
Input Voltage Range (Selectable)	170 – 280VAC (For PC); 90 – 280VAC (For Home Appliances)	
Nominal Input Frequency	50Hz / 60Hz (Auto sensing)	
OUTPUT		
Output Voltage Regulation	230VAC ± 10%	
Nominal Output Frequency	50Hz / 60Hz	
Waveform	Pure sine wave	
Transfer Time	10ms (For PC); 20ms (For Home Appliances)	
Surge Power	8000VA	12000VA
Peak Efficiency	95% at Line mode, 93% at Inverter mode	
BATTERY		
Nominal Battery Voltage	24VDC	48VDC
Floating Charging Voltage	27VDC	54VDC
Overcharge Protection	33VDC	63VDC
AC CHARGING & MPPT SOLAR CHARGING		
AC Charging Algorithm	3 step	
Max. PV Array Power	5000W	6000W
MPPT Operating Voltage Range	60 – 450VDC	
Max. PV Array Open Circuit Voltage	500VDC	
Max. PV Input Current	27A	
Max. AC Charging Current	100A	
Max. Charging Current	120A (AC charging plus solar charging)	
PHYSICAL & COMMUNICATION		
Dimension, D x W x H (mm)	119 × 313.6 × 457.5	
Net Weight (kg)	10	12
Communication Interface	USB, RS232, BMS, WiFi, Dry-contact	
ENVIRONMENT		
Humidity	5% – 95% Relative Humidity (Non-condensing)	
Operating Temperature	-10°C to 50°C	
Storage Temperature	-15°C to 60°C	

Specifications are subject to change without notice, all product drawings are for reference only.